


SE25T



2-way wood cabinet passive speakers, 100V/100W.

FEATURES 2-way wood cabinet passive speakers, 100V/100W. These speakers include a 12dB/Oct. passive crossover, with tweeter PTC electronic protection. These speakers have been expressly designed for near-field sound reinforcements applications: broadcasting, musicians personal monitors, conferences, theatres, etc. One professional multiwired connector guarantees a safe connection with minimal power loss.

Order code: PA SE25T

TECNICAL SPECS

Type	Wood passive speaker
Speaker/s	W: 2 x 5.25" T: 2" coaxial 2 ways
RMS power	100/50/25W
Constant voltage binding	100/70V
Frequency response	110Hz - 20KHz (-10dB)
SPL (1W/m)	93 dB
SPL MAX (Pmax @ 1m)	130 dB
Coverage Angle 1KHz/4KHz (-6dB)	V: 50° / 45°
Crossover Frequency	2.5KHz
Input/Output Connectors	1x Multiwired connector
Construction materials	15mm birch plywood with paint finish
Colour	Black
Dimensions (W x H x D)	165 x 445 x 170mm
Weight	7 kg (15.435 lb)
Fixing system	Bracket kit
Notes	Flying points: 2x M8 - 1x M10 on the rear

ACCESSORIES

Name

KPTED25B

KPTED8SB

SPSK290BK

Description

EDGE25PB wall mounting bracket. Black.

EDGE8PB wall mounting bracket with swivel joint. Black.

Mini aluminium stand for small speakers, supplied with screw locking system, steel security pin and "Air-Cushioned" air-damped device.