SE8T

2-way wood cabinet passive speakers,100V/100W.

FEATURES 2-way wood cabinet passive speakers, 100V/100W. This speaker include a 12dB/Oct. passive crossover, with PTC electronic protection for maximum reliability and speaker safe operation. One professional multiwired connector guarantees a safe connection with minimal power loss.

Order code: PA SE8T

TECNICAL SPECS

Type	Wood passive speaker
Speaker/s	W: 8" T: 2" coaxial 2 ways
RMS power	100/50/25W
Constant voltage binding	100/70V
Frequency response	63Hz - 20KHz (-10dB)
SPL (1W/m)	95 dB
SPL MAX (Pmax @ 1m)	115 dB
Coverage Angle 1KHz/4KHz (-6dB)	85º average
Crossover Frequency	2.5KHz
Input/Output Connectors	1x Multiwired connector
Construction materials	15mm birch plywood with paint finish
Colour	Black
Dimensions (W x H x D)	260 x 320 x 280mm
Weight	10 kg (22.050 lb)
Fixing system	Bracket kit / Floor stand / PA SPSK290BK
Notes	Flying points: 4x M10 on the rear

ACCESSORIES

Name	Description
KPTED8B	EDGE8PB wall mounting bracket. Black.
KPTED8SB	EDGE8PB wall mounting bracket with swivel joint. Black.
SPSK290BK	Mini aluminium stand for small speakers, supplied with screw locking system, steel security pin and "Air-Cushioned" air-damped device.